

# TRUCKS & BUSES

## Retread



## 3mm TREAD DEPTH

### What's so Important about 3mm Tread Depth?

Tyres with at least 3mm of tread depth might still be used for a short period before they are totally worn out. But if we remove tyres with at least 3mm tread depth and send them for retreading, they might be able to offer more mileage and provide better CPK (Cost Per Kilometre). So it's better to retread a tyre when it has at least 3mm tread left, than to use it until it is totally worn out.



3mm tread left

3mm



## 3x TYRE LIFE!

### What is 3x Tyre Life?

If you remove a tyre with at least 3mm tread depth and send them for retreading, you can achieve up to 3 TIMES the life\*. The casings of these tyres will not be damaged due to exposure of steel belt for Truck/Bus Radial Tyres, reducing the possibility of rust and dirt which may cause belt separation in radial tyres.

\* Above mileage data is for illustration purpose and is based on OTD=17mm for new and retread tyre. Actual mileage may differ depending on applications & mounting positions.

Assuming retread wear = 4,200km/mm



\*Casing retreadability depends on how well maintained the tyre is during operating conditions, such as proper inflation pressure, regular tyre checks, etc.

+ Assuming Total Wear Out is 17mm.



## EASY TO WORK HARD

**IF ONLY  
EVERYONE,  
OR EVERYTHING  
WORKED  
THIS HARD**

Ever wished you had a worker who could work day or night, in rain or shine, and never complained? Stop and take a look under your vehicles. For decades, Bridgestone has been the closest partner to the industrial segment, bearing the weight of the endless parade of trucks, trailers, forklifts, construction and mining machineries that roll on to build a better, stronger world. Hard work? Not at all!

### JL

J-LUG / J-LUG 2

- Designed for forklifts, trucks, shovel loaders and tractors
- Highly resistant to punctures

TYRE SIZE	PR	TYPE	TYRE SIZE	PR	TYPE
9.00-20	14	TT	250-15	16	TT
7.50-16	12	TT	7.00-12	12	TT
32X12.1-15	20	TT	4.50-12	8	TT
28X9-15	12	TT	6.50-10	12	TT
28X8-15	12	TT	6.50-10	10	TT
8.25-15	14	TT	21X8-9	14	TT
8.25-15	12	TT	21X8-9	10	TT
7.50-15	12	TT	6.00-9	10	TT
7.00-15	12	TT	5.00-8	10	TT
6.00-15	10	TT	5.00-8	8	TT
5.50-15	8	TT			
300-15	18	TT	*18X7-8	10	TT

\*JL2



TT: Tube Type T: Tubeless Type

## PJL

These puncnon tyres are “fully rubber compound filled”; no need to inflate air. It offers no puncture-trouble and sustains excellent wear on all kinds of surfaces.

TYRE SIZE	PR	TYPE
10.00-20	-	S
9.00-20	-	S
8.25-20	-	S
7.50-20	-	S
28X9-15	-	S
7.50-15	-	S
8.25-12	-	S
7.00-12	-	S
6.50-10	-	S
6.00-9	-	S

PUNCNON J-LUG



## RL

- Designed for heavy-duty straddle carriers and mobile cranes
- Offers excellent wear, cut and puncture resistance as well as strong traction on loose surfaces

TYRE SIZE	PR	TYPE
29.5-29	40	TT
21.00-25	36	TT
18.00-25	36	TT
12.00-24	20	TT
13.00-24	18	T
11.00-20	16	T

R-LUG



## PL01

- Designed for forklift tyre
- Fully rubber compound filled
- No need to inflate
- Resistant to puncture and excellent wear on all kinds of surfaces
- Made of special coloured rubber compound for durability and comfort
- Suitable for clean sites, for instance food, medicine, textile industries (CW and CG only)

PUNCNON LUG 01

TYRE SIZE	PR	TYPE	TYRE SIZE	PR	TYPE
7.50-16	-	S	23X9-10	-	S
28X9-15	-	S	6.50-10	-	S
8.25-15	-	S	21X8-9	-	CWS
7.00-15	-	S	6.00-9	-	S
6.00-15	-	S	15X4 1/2-8	-	S
5.50-15	-	S	18X7-8	-	S
300-15	-	S	5.00-8	-	S
250-15	-	S	4.00-8	-	S
7.00-12	-	S	3.50-5	-	S
4.50-12	-	S			

CW: White



TT: Tube Type T: Tubeless Type

## UL

- Designed for industrial vehicles, trucks, tractors, forklifts and shovel loaders

TYRE SIZE	PR	TYPE
12.00-24	16	TT
13.00-20	20	TT
12.00-20	20	TT
11.00-20	18	TT
11.00-20	16	TT
7.50-20	12	TT
7.00-20	10	TT
9.00-16	14	TT
8.25-15	14	TT
8.25-15	12	TT
8.25-12	12	TT
7.00-12	12	TT
4.50-12	8	TT
6.50-10	10	TT
6.00-9	10	TT
5.00-8	8	TT
4.00-8	6	TT
3.50-5	6	TT

### U-LUG



## YS

- Designed for straddle carriers and large trailers
- Features excellent wear resistance, stability and maneuverability

TYRE SIZE	PR	TYPE
13.00-20	20	TT
12.00-20	18	TT
12.00-20	16	TT
10.00-20	14	TT

### YARD SERVICE



## YS2

- Specially designed for straddle carriers
- Delivers excellent wear resistance for long serviceability as well as good traction and braking
- Wear indicators inserted around the tread's circumference allow for easy measuring of the tread depth in any position

TYRE SIZE	PR	TYPE
16.00-25	28	TT
16.00-25	28	TT
14.00-24	24	TT

### YARD SERVICE 2



TT: Tube Type T: Tubeless Type