



**ALLIANCE
 AGRICULTURE**

TRA: **R-4**
 Speed Rating: **G**

Alliance 317 tire is designed for applications that require high traction. It is engineered to provide the best performance for on and off road services in tough weather conditions. The tire provides excellent traction to drive wheels and has a strong nylon carcass construction.

IMPLEMENT - 10.5/80-18

| Size | Rim | Unloaded Dimension | | Loaded Static radius mm | Rolling Circumference mm | Load Index PR Symbols | Inflation Pressure bar | Recommended Load | | | | | | | |
|------------|-----|--------------------|-------|-------------------------|--------------------------|----------------------------------|------------------------|------------------|---------|---------|---------|--------------|---------|---------|---------|
| | | SW mm | OD mm | | | | | Speed | | | | | | | |
| | | | | | | | | Drive wheel | | | | Free rolling | | | |
| | | | | | | | | 10 kmph | 20 kmph | 30 kmph | 40 kmph | 10 kmph | 20 kmph | 30 kmph | 40 kmph |
| 10.5/80-18 | 9 | 274 | 907 | 408 | 2670 | 6PR | 2.2 | 1290 | 1140 | 1000 | 900 | 1870 | 1650 | 1450 | 1310 |
| | | | | | | 121A6 118A8 108A6 104A8 | | | | | | | | | |
| | | | | | | 10PR | 3.7 | 1750 | 1550 | 1360 | 1220 | 2520 | 2220 | 1950 | 1760 |
| | | | | | | 131A6 127A8 119A6 115A8 | | | | | | | | | |

In this size
 6PR is no
 longer active
 for production

