



**ALLIANCE
 AGRICULTURE**

TRA: **R-1W**
 Speed Rating: **A8**

The Alliance FarmPRO 70 Series Radial is a highly versatile range that represents the family of modern agricultural radial tires. The multi angle lug design with steep angles at the center enables smooth ride, along with self clearing characteristic. In addition, the shallow angle at shoulder provides superior traction. These tires are characterized by reinforced construction in the bead area and have enhanced bead to bead distance to facilitate perfect fit on the rim. The regular cavity in the tread design ensures a straighter sidewall which enhances the tires visual appeal.

TRACTOR - 280/70R20

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load					
		SW mm	OD mm					Speed					
								Mixed application					
								Static kmph	10 kmph	25 kmph	30 kmph	40 kmph	50 kmph
280/70R20	W10, W9	278	912	415	2706	116A8 116B	1	1730	1130	830	800	750	750
							1.2	1910	1250	920	890	830	830
							1.4	2090	1370	1010	970	910	910
							2.4	2880	1880	1390	1340	1250	1250

*Alliance allows for free rolling application: Load capacity to be increased by 20%, after increasing the inflation pressure by 20%

