



**ALLIANCE
 CONSTRUCTION &
 INDUSTRIAL**

TRA: **R-4**
 Speed Rating: **A8**

Alliance 325 ToughTrac tire is designed for heavy duty applications with very good resistance to shock and perforation. This tire has specially designed directional tread pattern with massive lug design, aggressive tread pattern and flat stable crown having extra thick sidewall and under tread, making it ideal for compact machineries.



STEEL
 BELTED



HEAT
 RESISTANT
 COMPOUND

FRONT BACKHOE - 400/80-24 Steel Belted

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load				
								Speed				
		Mixed application										
		Static kmph	10 kmph					25 kmph	30 kmph	40 kmph		
400/80-24	DW13	404	1250	568	3725	162A8	5	10930	5940	5040	4940	4750

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load				
								Speed				
		Mixed application										
		Static kmph	10 kmph					25 kmph	30 kmph	40 kmph		
400/80-24	DW13	404	1250	568	3725	162A8	5	10930	5940	5040	4940	4750

Steel belt available in 162 A8 only

