



Ecosolid

RESILIENT - LOW INTENSITY APPLICATIONS

Main Benefits

- Deep tread design
 For enhanced tire life and heavy ground traction.
- Enhanced stability
 Faster load positioning and cornering.
- Energy efficiency
 Low rolling resistance for improved energy efficiency.

Polymer Engineering, Application Expertise

Trelleborg strives to deliver optimum performance for all our customers. We offer problem-solving products in our premium range. Contact our application specialists to learn more about our latest tire solutions.



STABILITY





BATTERY LIFE



OVERHEATING



VIBRATION TIRE

©

TIRE CRACKING



EXPLOSION RISK



Special compounds available





RESILIENT - LOW INTENSITY APPLICATIONS



Size	Alternative Size	Rim	Tire type & Compound availability STD LOC BOTH		Dimensions nm] Section Width	Load Capacity [kg] Other Counterbala Trucks up to		o 25 km/h Steering
15x4½-8	125/75-8	3.00D-8	Ē ▼	372	103	1,210	1,040	Wheel 800
5.00-8	120/100	3.00D-8	▼	457	122	1,650	1,415	1,090
16x6-8	150/75-8	4.33R-8	▼	408	143	1,740	1,495	1,150
18x7-8	180/70-8	4.33R-8	· ▼	450	143	2,490	2,145	1,650
140/55-9	15x5.5-9	4.00E-9	· ▼	370	127	1,360	1,170	900
6.00-9	13/3.3 3	4.00E-9	· ▼	508	140	2,190	1,885	1,450
21x8-9	200/75-9	6.00E-9	· · · · · · · · · · · · · · · · · · ·	508	185	3,200	2,755	2,120
6.50-10	200/13-9	5.00F-10	,		163		·	
				559		2,720	2,340	1,800
200/50-10		6.50F-10	▼	447	186	2,870	2,470	1,900
23x9-10	225/75-10	6.50F-10	▼	571	190	4,000	3,445	2,650
7.00-12		5.00S-12	▼	660	168	3,380	2,920	2,240
23x10-12	250/60-12	8.00G-12	▼	571	224	4,380	3,770	2,900
27x10-12	250/75-12	8.00G-12	▼	656	230	4,530	3,900	3,000
7.00-15		5.5-15	▼	711	178	4,115	3,545	2,725
8.25-15		6.5-15	▼	787	206	5,510	4,750	3,650
28x9-15	225/75-15 (8.15-15)	7.0-15	•	686	204	4,000	3,445	2,650
250-15	250/70-15	7.0-15	•	704	216	5,510	4,745	3,650
300-15	315/70-15	8.0-15	•	812	254	6,795	5,850	4,500
355/65-15	32x12½-15(350-15)	9.75-15	•	809	278	9,060	7,800	6,000







