



**ALLIANCE  
 CONSTRUCTION &  
 INDUSTRIAL**

TRA: **R-3**  
 Speed Rating: **A8**

The Alliance 329 is a diamond tread design tire built with a strong nylon construction. Its wide and extended tread protects shoulders and sidewalls against cutting and side snagging. The special cut and chip resistant compound, heat resistant compound and the tires strong nylon construction provide long life to the tire.

**TRACTOR - 23.1-26**

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load								
		Speed														
		Field operation						Not high and sustained torque; Road transport								
		High Tor	Low Torque													
		SW mm	OD mm				10 kmph	10 kmph	20 kmph	Static kmph	10 kmph	25 kmph	30 kmph	40 kmph	50 kmph	
23.1-26	<b>DW20</b>	587	1580	697	4600	8PR	0.9	2760	3610	3100	5930	3870	2860	2760	2580	2350
						145A8	1	2930	3840	3290	6300	4110	3040	2930	2740	2490
							1.1	3100	4060	3480	<b>6670</b>	4350	3220	3100	<b>2900</b>	2640
						10PR	1.2	3180	4160	3560	6830	4460	3300	3180	2970	2700
							149A8	1.3	3330	4350	3730	7150	4670	3450	3330	3110
						1.4		3480	4550	3900	7480	4880	3610	3480	<b>3250</b>	2960
						12PR	1.5	3630	4750	4070	7800	5090	3760	3630	3390	3080
						153A8	1.7	3910	5110	4380	8400	5480	4050	3910	<b>3650</b>	3320
						16PR	1.9	4180	5470	4690	8990	5870	4340	4180	3910	3560
						159A8	2.1	4440	5810	4980	9550	6230	4610	4440	4150	3780
2.3	4680	6130	5250	10060	6560		4860	4680	<b>4375</b>	3980						

Note: For above mentioned size 8 PR is no longer active for production. Recommended rim in red (Bold)

